

Motorbike 4T 10W-40 Street

Description

High-performance motor oil based on synthetic technology. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear are just as much taken for granted as gentle clutch engagement and disengagement and gear shifting. Tested on engines with catalytic converters.

Properties

- guarantees low oil consumption
- high shear stability
- high wear resistance
- optimum stability to aging
- optimum lubrication under all operating conditions
- outstanding engine cleanliness
- tested for the use with catalytic converters
- especially suitable for wet clutches

Approvals

API SN PLUS • JASO MA2

Technical data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,86 g/cm ³ DIN 51757
Viscosity at 40 °C	96 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,6 mm ² /s ASTM D 7042-04
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D 5293
Viscosity index	158 DIN ISO 2909
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	10 % ASTM D 5800-08 Method B
Flash point	238 °C DIN ISO 2592
Total base number	7,6 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049

Areas of application

Developed for air and water-cooled 4-stroke engines



exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

Application

The operating instructions of the engine manufacturers must be followed.

Note: Optimum effectiveness only when the product is used on its own (i.e. no mixing).

Available pack sizes

1 l Canister plastic	1521 D-BOOKLET
1 l Canister plastic	1755 JP
1 l Canister plastic	21246 ALGERIEN-GB-ARAB-F
4 l Canister plastic	1243 D-BOOKLET
20 l Canister plastic	1562 D-GB
20 l Canister plastic	20854 JP
60 l Drum sheet metal	1563 D-GB
205 l Drum sheet metal	1568 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.